



德力西电气有限公司

Product Specification

产品规格书

Model: DHAZL5015H24B

Factory Address: Delixi High Tech Park, LiuShi Town, Yueqing City,
Zhejiang Province

工厂地址：浙江省乐清市柳市镇德力西高科技工业园

Tel: +086-400-826-8008

电话：+086-400-826-8008

Website: www.delixi-electric.com

网址： www.delixi-electric.com



SPECIFICATION 规格参数

1	Dimension 外形尺寸	50*50*15mm
2	Bearing System 轴承类别	Ball bearing
3	Rated Voltage 额定电压	24 VDC
4	Operating Voltage 工作电压	12-26.4 VDC
5	Starting Voltage 启动电压	12 VDC
6	Input Current 电流	0.05 A
7	Input Power (MAX) 功率(最大)	1.2 W
8	Speed 额定转速	6000 RPM
9	Rated Current 额定电流	0.05 A
10	Air Flow (MAX) 风量 (最大)	14.52 CFM
11	Static Air Pressure (max) 风压 (最大)	4.21 mmH2O
12	Noise Level 噪音	36 dBA
13	Signal Output 信号输出	NO
14	Auto Restart 自动重启	YES
15	PWM Speed Control	NO
16	Life Expectance (L10) 预期寿命	70,000Hours / 25°C
17	Rotation 叶片转动方向	Counterclockwise:逆时针
18	Lead Wire 引出线规格	1007/26AWG *300mm
19	Housing 端子头	无端
20	Net Weight 净重	28 g
21	Protection class 防护等级	NO

1. 外观尺寸(External dimensions)

1.1 参考附图样(Refer to drawing)

2. 特性规格(Characteristics)

2.1 运转温度: $-20^{\circ}\text{C}\sim 70^{\circ}\text{C}/66\%(\text{RH})$

Operating temperature: $-20^{\circ}\text{C}\sim 70^{\circ}\text{C}/66\%(\text{RH})$

2.2 储存温度: $-30^{\circ}\text{C}\sim 70^{\circ}\text{C}/66\%(\text{RH})$

Storage temperature: $-30^{\circ}\text{C}\sim 70^{\circ}\text{C}/66\%(\text{RH})$

2.3 绝缘耐压强度: 能承受得住在本体与两条电源线间加500V交流电压1秒5MA。

Dielectric strength: Must Withstand 500 VAC 1second 5MA between housing and both lead wires.



2.4 绝缘阻抗强度：在本体与两条电源线间加500V直流电压之绝缘阻抗10M。

Insulation resistance: Between housing and both lead wires at least 10M.

2.5 电源线抗拉强度：每条线以二公斤的拉力扯15秒，不会断裂。

Tension strength of lead wire not broken at 1kg for 15sec per piece.

3.6 定义(Definition)

3.6.1 起动电压：是指当风扇突然通电后能够使风扇起动之最小电压。

Start voltage is the least voltage that enable to start the fan by sudden power on.

3.7 保护功能(Protection)

3.7.1 风扇锁定测试：风扇锁定72小时，在解除锁定后仍能正常运转。

Fan locked test: Fan locked 72hrs.it remains to work normally after lock release.

3.7.2 反向电压测试：以额定电压作反向导电测试15分钟后，再正向导电仍可正常运转。

Reversal voltage test: Reversal voltage test at Rated Voltage for 15 minutes and all lead to fall running. But,it became running normally again right after correcting voltage.



4. 主要材料/零件规格(Main Materials/ parts Specification)

材料/零件(Materials/ Parts)		材质规格(Specification)	备注 Remark
4.1	外框 (Plastic Material)	a. 94-V0 b. P. B. T+15%GF Black	
4.2	扇叶(Blade housing)	a. 94- V0 b. P. B. T+15%GF Black	
4.3	绝缘架(Bobbin)	a. 94-V0 b. P. B. T+15%GF Black	
4.4	轴芯 (Stator core)	不锈钢 Stainless steel (SUS420J2)	
4.5	轴承 (Bearing)	滚珠轴承 TWO BALL	
4.6	橡胶磁铁 (Rubber magnet)	铁锶粉末化合物 Strontium ferrite (BQB14W)	
4.7	矽钢片 (Silicon steel strip)	H50	
4.8	漆包线 (Enamelled copper wires)	MW-2UEW 耐热. 150℃	
4.9	印刷电路板 (Printed Circuit Board)	单层印刷电路板 94- HB Wiring printed single layer board	
4.10	电源线 (Lead Wire)	1007#24AWG 线芯材质: 镀锡铜	
4.11	连接器 (Connector housing)		
4.12	贴纸 Label	底标	

产品尺寸图

